



# Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom (9W1A6AA)



## Overview

### Harness the power of focus

Keep presentations engaging with the Poly Studio E60 smart MPTZ optical zoom camera. The main presenter is always in frame, and every person in the room is shown with exceptional accuracy, even at the far end. With every detail captured, presentations are easier to follow.

### Zoom in on all the details

Whether in person or remote, keep your teams engaged no matter where they're seated. Make sure they pick up on every detail with true-life definition including small gestures and expressions even in large rooms with a 12x optical zoom.

### A simplified setup and easy to use

Kickstart meetings without delays and make every minute count with the Poly Studio E60 smart optical zoom camera. Its flexible connectivity and compatibility with top conferencing platforms simplifies things so you can solely focus on your presentation.

### Distractions out. Engagement in

The Poly Studio E60 smart optical zoom camera lets everyone see what's going on in the room. Presenter tracking and AI-driven framing modes make sure the focus stays on the all-important action so nobody misses a beat, no matter where they are.

### Making IT's job a little easier

Poly Lens<sup>[1]</sup>, remote device management, gives you better visibility into workspaces across the entire organization. IT professionals can remotely monitor and troubleshoot Poly devices as well as streamline applying bulk software and policies.

# Features

## Keep the focus right where it belongs

Eyes for everyone. With a 12x optical zoom, the Poly Studio E60 smart MPTZ optical zoom camera can zero in on every detail and pick up content with amazing clarity, ensuring a deeper connection, and letting nothing escape its view.

## Keep the presenter center-stage

Poly DirectorAI presenter tracking keeps the main speaker in focus during presentations, lessons, or speeches. It zooms in and follows them in real-time for a seamless, engaging virtual experience with minimal distractions.

## Catch every detail in 4K

The ultra-HD imaging system and 4K sensors deliver stunningly detailed and sharp images for a visual experience that feels lifelike and true to reality, and makes virtual attendees feel more included and engaged.

## In frame. In focus. Engaged

Keep all participants in-frame and engaged with Poly DirectorAI group framing. It smartly captures the entire group on screen, removing excess space and adjusting the angle for equal visibility. With everyone in frame, no one gets left out.

## No elaborate or complex set up

IT will find the Poly Studio E60 smart MPTZ optical zoom camera easy to install on a monitor, wall, or ceiling. Its user-friendly setup allows for convenient and flexible connections over IP or USB.

## Works with your platform of choice

An IT manager's dream, the Poly Studio E60 smart MPTZ optical zoom camera was created for communication and is optimized and certified to work with top virtual meeting providers.

---

*[1] Poly Lens software capabilities are limited to Poly devices and select HP cameras. For the most up to date list of supported devices you may check the support list here: <https://info.lens.poly.com/docs/begin/supported-devices>.*

## Specifications

<b>Dimensions (W x D x H)</b>	20 x 15 x 16.5 cm
<b>Dimensions (W x D x H)</b>	7.87 x 5.9 x 6.49 in
<b>Weight</b>	1.79 kg
<b>Weight</b>	3.96 lb
<b>Ports</b>	1 USB-B; 1 RJ-45 (10/100/1000 Mbps) Ethernet interface (supporting PoE+ power supply); AC/DC power jack <sup>[2,3]</sup>
<b>Package dimensions (W x D x H)</b>	29.5 x 24.5 x 24.2 cm
<b>Package weight</b>	3987 g
<b>Power supply type</b>	External
<b>UPC number</b>	(AB2) 198122304370; (AC3) 198122304387
<b>Manufacturer Warranty</b>	Poly standard one-year limited warranty
<b>What's in the box</b>	Ethernet cable (5 m); Wall mount kit; Quick start guide; Warranty card; Poly Studio E60; USB-B to USB Type-A cable (2 m); IR remote control

## Additional specifications

<b>Cable length</b>	2 m
<b>Cable length (imperial)</b>	6.56 ft
<b>Camera features</b>	Motorized pan ( $\pm 170^\circ$ ), tilt ( $\pm 30^\circ$ ) and zoom (MPTZ)
<b>Camera range (imperial)</b>	Up to 32.8 ft
<b>Camera range (metric)</b>	Up to 10 m
<b>Camera resolution</b>	2160p, 4K UHD (3840 x 2160)
<b>Camera type</b>	Dual-lens
<b>Cartons per layer</b>	4
<b>Cartons per pallet</b>	20
<b>Certified collaboration software</b>	Tencent; Microsoft Teams; Zoom
<b>Color</b>	Black
<b>Compatible Operating Systems</b>	Android; Windows
<b>Content video resolution (input)</b>	UHD (3840 x 2160)
<b>Content video resolution (output)</b>	UHD (3840 x 2160)
<b>Country of origin</b>	Canada(AC3); China(AB2, AC3); Côte d'Ivoire(AC3); Fiji(AC3); Laos(AC3); Lesotho(AC3); Mexico(AC3)
<b>Datasheet photo 1</b>	AHID/413b7f0db8d12f285299bc178d41329a6e5f10c2
<b>Datasheet photo 2</b>	AHID/e97833c16fa94fd2c168bce526272b9b3a694fc5
<b>Datasheet photo 3</b>	AHID/0fbb119c64092fb8c7fea03843de75dcde15d24e
<b>Diagonal field of view (dFoV)</b>	78.1° (PTZ camera)
<b>Focus type</b>	Auto focus
<b>Horizontal field of view (hFoV)</b>	71° (PTZ camera); 107° (panoramic camera)
<b>Lens cover capabilities</b>	Attachable; Face away
<b>Management Software</b>	Poly Lens
<b>Microphone type</b>	Two-microphone element beamforming array
<b>Multiple order quantity</b>	1
<b>Network capabilities</b>	1 10/100/1000 Mbps Ethernet supporting POE+/PSE
<b>Non-operating temperature - Celsius</b>	-40 to 70 °C
<b>Non-operating temperature - fahrenheit</b>	40 to 158 °F
<b>Operating temperature range</b>	32 to 104 °F
<b>Operating temperature range</b>	0 to 40°C
<b>Package dimensions (W x D x H)</b>	11.6 x 9.65 x 10.4 in

<b>Package weight</b>	8.8 lb
<b>Pallet (layers)</b>	5
<b>Pallet weight</b>	378 kg
<b>Pallet weight</b>	833.34 lb
<b>People video resolution</b>	4K, 30 fps (TX and RX) from 2048 Kbps
<b>Physical security</b>	Standard Kensington lock slot
<b>Power</b>	AC/DC 12 V; Power over Ethernet (PoE+) injector <sup>[1]</sup>
<b>Products per pallet</b>	80
<b>Products per pallet layer</b>	16
<b>Sensor size</b>	1/2.8 inch CMOS sensor
<b>Smart camera technology</b>	Group framing; Presenter tracking; Poly DirectorAI
<b>Total camera resolution (megapixels)</b>	2 x 8 MP
<b>UNSPSC code</b>	45121520
<b>Video frame rate</b>	30 fps (up to 4K resolution)
<b>Zoom capability</b>	12x optical

---

*[1] Sold separately.*

*[2] It connects over IP only with Poly Studio G62 and Poly G7500.*

*[3] IP connection supports up to 1080p.*

---

## Services

### Communication & Collaboration

★ : Recommended

#### Poly Support Services

1 Year Partner Poly+ Onsite Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom	U86LNPV
1 Year Partner Poly+ Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom	U86LFPV
1 Year Poly+ Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom	U86LCPV
3 Year Partner Poly+ Onsite Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom	U86LQPV
3 Year Partner Poly+ Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom	U86LGPV
3 Year Poly+ Poly Studio E60 Smart Camera 4K MPTZ with 12x Optical Zoom	U86LDPV

# Hybrid Work Solutions

## Video

★ : Recommended

### Video Accessories

Poly Studio E60 Ceiling Mount	9W1A8AA
Poly Studio E60 Power Accessory	9W1A9AA
Poly Video IEC Power Cord	874T5AA

---

## Disclaimer — Copyright

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (ww-en) – May 19, 2025 7:00 AM UTC+0000